



2 MP HDMI Network Cameras



FEATURES

- FLASH : 512MB , DDR : 1GB , 2MP@25/30fps high resolution
- Quad core ARM Cortex-A7 and RISC-V MCU , 2.0Tops NPU
- Real time display of monitoring videos, storage capacity up to 1TB
- Deterrence methods: real-time video, deterrence image
- Pop-up deterrence image when detected person by AI/motion or alarm in triggering signal
- Support CMS batch management: device setting and/or upload LOGO deterrence image
- Support HDMI display : LOGO、deterrence image
- Support face tracking box on screen

DIMENSION



SPECIFICATIONS

CIR-HBS6GMSD

Camera

IP Rating	IP67
Filter	Removable IR Cut Filter
Image Sensor	1/2.9" 2M Progressive Scan CMOS
Lens	2.8mm IR Lens
Resolution	1920(H)×1080(V)
Electronic Shutter	NTSC:1/30-1/100,000s PAL:1/25-1/100,000s
Min Illumination	0Lux
Available IR Range	15-20M

Video/Audio

Video Compression	H.264 / H.265
Transmission Stream Rate	Dual Stream (Code Rate:36Kb~16M)
Frame Rate	1~25fps (PAL) ,1~30fps (NTSC)
Audio Compression	G711A、G711U

External Interface

HDMI1.4	1080P/30FPS
Network Interface	RJ45*1 10M/100M
Audio Interface	input/output*1
Alarm Interface	input/output*1

Network

Protocol	IPv4, IPv6,DHCP ,HTTP ,Onvif ,DNS ,DDNS ,FTP ,UPNP , RTSP , SMTP , NTP
Network Support	ONVIF Profile S , API
Maximum Users	10
Web Language	English, Simplified Chinese, Traditional Chinese

Function

Image Setting	Contrast, Brightness, Sharpness, Saturation, WDR, 3DNR, HLC, BLC
Storage	NVR、VMS、TF Card (MAX 1TB)
Video Type	Manual, Timing, Motion Detection , Alarm Video
Alarm Triggers	Motion Detection, Alarm
Alarm Event	Snapshot, Video, Alarm Output, Email Upload,
System/Explorer Support	Chrome, Firefox, Safari, IE
General Function	Flashing,Mirror, OSD information overlay、Camera angle

General

Power Supply	DC12V±10% , POE
Current Consumption	IR On: 510mA(Max) IR Off: 310mA(Max)
Dimension	Ø114×82mm
Weight	600g
Storage Temperature	-30 ~ +60°C
Operating Temperature	-30 ~ +40°C

